



TC1542 Conveyor Specifications

Conveyor Size	TC1542
Conveyor Length	42'
Conveyor Weight	2,000 lbs.
Lowered Conveyor Reach (C)	15 1/2"
Raised Conveyor Reach (D)	15 3/4"
Maximum Height Extension @ 30° (A)	20 1/2"
Transport Height (B) c/w Hitch @ 12"	13 1/2"
Wheel Transport Width	112"
Tube Thickness	14ga
Belt Width	15"
Belt Type	PVC, Crescent Top
Drive System	Top Drive
Min. Horsepower (Electric)	10 to 15
Lift Mechanism	Cable
Frame Arms	3 1/2" x 11 ga
Axle Tube Size	2 1/2" x 2 1/2" x 3/16"
Tire Size	165/72 x 13
Hopper Style	Standard
Hopper Width & Length	36" x 37"
Collapsed Hopper Height	19 1/2"
Extended Hopper Height	34"
Capacity (Approx.) *	3,600 BPH

*Maximum capacity as tested with corn.

Features

- Gentle on seed
- Quiet operation
- 6" Vulcanized drive rollers
- Spring loaded, folding hopper
- Patent pending hopper is able to open, allowing more thorough cleanout
- Conveyor belt tensioner is located at the inlet end for ease of adjustment
- Fully enclosed with wind guards to avoid spills
- Removable Hitch
- Brushes inside discharge head to catch material trying to return with the belt
- Heavy duty 1 1/4" shafts and greasable bearings on the driver pulley and the tensioner pulley
- Cold weather belt and rollers
- New tires
- Seed Certified

Options

- Hydraulic winch
- TC15 Wheel kit
- TC15 Low profile hopper
- Flex spout



Bottom hopper lid opens up for Total Clean Out.

- Seed Certified
- Patent Pending
- Total Clean Out™